Weight-
Approx. 21.5kg (23.14 Kg w/consumables)

404mm
480mm
428mm

EPSON AcuLaser™
M4000N

CONSUMABLES

IMAGING CARTRIDGE	(20,000 pages*6*7) C13S051170
RETURN IMAGING CARTRIDGE	(20,000 pages*6*7) C13S051173
FUSER UNIT (220 - 240V)	(200,000 pages*6*7) C13S053038

*1 From Standby mode
*2 The duration between the power being turned on and [Ready] being displayed is 17 seconds or less (at 23ºC and 55% RH, with rated voltage and standard memory).
*3 The duration to recover from sleep mode till [Ready] is displayed is 17 seconds or less (at 23ºC and 55% RH, with rated voltage).
*4 Weight including Imaging Cartridges.
*5 For Euro only
*6 The figures are approximate number of sheets pointed under conditions of continuous printing on A4 size paper with ISO 19752 pattern.
*7 Depending on various usages and environments page yield may reduce and come to its end of service life. It may occur even wth toner left due to reaching the other parts' end of service life.

PRINTER TYPE

PRINTING TECHNOLOGY	Laser
RESOLUTION	1200dpi
PRINT SPEED	43ppm / 26.4ppm (Simplex/Duplex)
FIRST PAGE OUT	7.9 sec*1
WARM UP TIME	17 sec*2*3
MAXIMUM MONTHLY VOLUME	200,000 pages

PAPER HANDLING

STANDARD PAPER INPUT		700 sheets (150 Multi Purpose Tray + 550-sheet Cassette Unit)
MULTI PURPOSE TRAY	PAPER SIZE	A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4, C5, C6, DL, Com10, Monarch, IB5
	WIDTH	76.2 - 215.9 mm
	LENGTH	127.0 - 355.6 mm
	PAPER WEIGHT	64 - 216 g/m^2
550-SHEER PAPER CASSETTE UNIT	PAPER SIZE	A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4, C6, DL, Com10, Monarch, IB5
	PAPER WEIGHT	64 - 216 g/m^2
550-SHEER PAPER CASSETTE UNIT (OPTION)	PAPER SIZE	Same as Standard Paper Cassette
	PAPER WEIGHT	Same as Standard Paper Cassette
DUPLEX UNIT (OPTION)	PAPER SIZE	A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4
	PAPER WEIGHT	64 - 216g/m^2
MAXIMUM PAPER INPUT		1800 sheets (150 MP Tray + 550 Sheet Paper Cassette + 2x extra 550 Sheet Paper Cassette)
PAPER OUTPUT STANDARD/MAXIMUM		500 sheets (Face Down), 70 sheets (Face Up)
PAPER OUTPUT STANDARD/MAXIMUM (OPTION)		500 sheets (Stacker)

INTERFACES

Hi-Speed USB (2.0 compatible), Parallel Interface (IEEE 1284), and 10/100 Base TX Ethernet Interface

MEMORY

STANDARD/MAXIMUM	64 MB / 576 MB

POWER REQUIREMENT

ENERGY STAR COMPLIANT		
RATED FREQUENCY		50Hz / 60Hz (220 - 240V)
RATED CURRENT		5.5A / 11A (220 - 240V)
POWER CONSUMPTION	OPERATING	Max. 1120 Wh / 1090 Wh (220 - 240V) Ave. 654 Wh (220 - 240V)
	STANDBY	77 Wh / 78 Wh (220 - 240V)
	SLEEP	10 Wh / 7Wh (220 - 240V)

ENVIRONMENTAL CONDITIONS

TEMPERATURE	OPERATION	10 to 32ºC
	STORAGE	0 to 35ºC
HUMIDITY	OPERATION	15 to 85% RH
	STORAGE	15 to 80% RH
SOUND POWER	OPERATING	7.25 B (A)
	STANDBY	5.3 B (A)
SOUND PRESSURE	OPERATING	56.1 dB (A)
	STANDBY	28 dB (A)

DIMENSION AND WEIGHT*4

AL-M4000N	428 x 480 x 404 mm, 21.5 Kg (23.14 Kg w / consumables)
AL-M4000N with 550-sheet Paper Cassette	428 x 480 x 499 mm, 27.8 Kg (29.44 Kg w / consumables)
AL-M4000N with 2x 550-sheet Paper Cassette	428 x 480 x 589 mm, 34.1 Kg (35.74 Kg w / consumables)
AL-M4000N with Duplex Unit	428 x 572 x 404 mm, 23.4 Kg (25.04 Kg w / consumables)
AL-M4000N with Stacker	428 x 480 x 539 mm, 24.1 Kg (25.74 Kg w / consumables)
AL-M4000N with 550-sheet Paper Cassette and Stacker	428 x 480 x 634 mm, 30.4 Kg (32.04 Kg w / consumables)
AL-M4000N with 2x 550-sheet Paper Cassette and Stacker	428 x 480 x 724 mm, 36.7 Kg (38.34 Kg w / consumables)
AL-M4000N with 2x 550-sheet Paper Cassette, Duplex Unit and Stacker	428 x 572 x 724 mm, 38.6 Kg (40.24 Kg w / consumables)

PRINTER DRIVER/UTILITY

PRINTER DRIVER	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
EPSON STATUS MONITOR	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
POSTSCRIPT® PRINTER DRIVER	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
EPSON SCREEN FONT	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
EPSON BARCODE FONTS	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
EPSONNET PRINT	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
EPSONNET CONFIGURATION	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
EPSONNET EASYINSTALL	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
EPSON WEB-TO-PAGE	Microsoft® Windows® 2000/XP
JAVA RUNTIME ENVIRONMENT SE	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
USER GUIDES	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
DATA FILE FOR*5	Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64

PRINTER CONTROL LANGUAGE EMULATIONS

STANDARD	ESC/Page™, ESC/P2™, FX 1239X, PCL5e, PCL6, A-PS (Level 3), PDF 1.3

RESIDENT TYPEFACES

SCALABLE	84 ESC / Page, 95 PCL5c, 80 PCL6, 17 PS3
BITMAP	7 ESC / Page, 5 PCL5c, 1 PCL6
TYPEFACE	10 ESC / P2, 8 FX, 8I239X

OPTIONS

550-SHEET PAPER CASSETTE UNIT	C12C802471
DUPLEX UNIT	C12C802481
STACKER	C12C802111
HARDDISK	C12C824172
DIMM MEMORY 64MB RAM (90 pin)	7100742
DIMM MEMORY 128MB RAM (90 pin)	7100744
DIMM MEMORY 256MB RAM (90 pin)	7102850

EPSON
EXCEED YOUR VISION

INDIA - (91) 80-305-15000, CALCUTTA - 228 31589/90, CHENNAI - 302 77500, MUMBAI - 282 61515/16/17, NEW DELHI - 306 15000
INDONESIA - (62) 21-572-3161
MALAYSIA - (60) 3-562-88288
PHILIPPINES - (632) 706-2663
SINGAPORE - (65) 6586-5500, (65) 6586-3111
THAILAND / INDOCHINA - (662) 685-9888

Dealer's Stamp